

200# DUMBWAITER SPECIFICATIONS

DESIGN	Floor loading or Counter height
CAR	Custom Size and Shape with collapsible gate on each opening
SIZE	Up to 14.25 cubic feet
MATERIAL	Carbon Steel (Stainless Steel Available)
OPENING	One, two or three sides available
CAPACITY	200 lbs
SPEED	33 fpm
POWER	220 volt, 15 Amp
POWER UNIT LOCATION	Located overhead, underneath, or adjacent to shaft
WINDING DRUM	High torque 3/4 hp. electric motor and completely enclosed worm gear, drums threaded to accommodate a single 1/4" x 8 x 19 WSC wire rope
MAGNETIC BRAKE	Mechanically applied, electrically released only when motor is running
GUIDE RAIL	Monorail type, "C" Channel
CONTROLS	Fully automatic allowing car to be sent or called from any floor. Terminal limit switch provided for top final. Car stops automatically at landing levels. Door interlocks for hoistway doors to prevent operation of the dumbwaiter unless doors are closed and to prevent opening of any door except when the car is at that landing.
OPTIONAL EQUIPMENT	Light in car, In-use lights, machine limit, arrival lights, arrival gong, door open alarm, time delay relay, auxiliary car stabilizing rollers, removable adjustable shelves, key switch operation, laminate floor.